
User's Manual

Loss Simulator v1.0
Document version 1.0

INTRODUCTION

The Loss Simulator is an application intended to estimate power losses of Power Modules, IPM. The software computes this power loss values using 3 sections of inputs.

1. Module/Device Parameter
2. Circuit Algorithm
3. User Input Conditions/Parameters

When computation finished, the software will provide 2 outputs

1. Power Loss Result display
2. CSV export of step by step computation




RECOMMENDED SYSTEM REQUIREMENTS


Operating System	Microsoft Windows XP, Microsoft Windows Vista, Microsoft Windows 7 32-bit & 64-bit, Microsoft Windows 8 32-bit & 64-bit
Memory	1GB or better
Screen Resolution	At least 800 x 600

EASY INSTALLATION


1. Copy and Paste the zip file to the target directory



2. Unzip the file




3. Open the folder and run the Loss Simulator Application



NOTE: Simply delete the whole folder of the application to remove/uninstall the software.

USING THE SOFTWARE

Input Window



A. Module/Device

- Select a Module or Device to be estimated
- If no Module is selected, computation is not available.

B. Circuit

- Select a type of circuit to be used for the selected device
- If no Circuit is selected, computation is not available

C. Gate Resistor

- Select the gate resistor of the device to be used
- If no Gate resistor is selected, the default gate resistor of the module/device will be used.

D. V_{CC} (P-N Voltage)

- Used by recommended operation conditions although it is calculated.

- Value must be greater than or equal to Zero only ($V_{CC} \geq 0$).

E. I_O (Output Current)

- Used by recommended operation conditions although it is calculated.
- Value must be greater than or equal to Zero only ($I_O \geq 0$).

F. Current Setup

- I_{PEAK}
- A_{RMS}

G. PF (Power Factor)

- Value is ranging from -1 to 1 only ($-1 \leq PF \leq 1$).

H. Mod (Modulation Ratio)

- Available only for 3-Phase Inverter
- Value is ranging from 0 to 1 only ($0 \leq Mod \leq 1$).

I. Duty (Duty Cycle)

- Available only for Chopper
- Value is ranging from 0 to 100 only ($0 \leq Duty \leq 100$).

J. F_C (Carrier Frequency)

- Value must be greater than or equal to One only ($F_C \geq 1$).

K. T_F (Heat Sink Temperature)

- Used by module case temperature although it is calculated
- Error message will appear if T_j is over Junction Temperature



L. Execute

- Start the computation
- Software can't exit during computation.

M. Stop

- Stop the ongoing computation
- All controls will be disabled aside from "Stop" Button during computation

example: 3 phase Inverter circuit diagram



Output Window

Loss Simulator v1.0

Input **Output**

A **Tr**

P-Tr	41.526776	W/Tr
SW	4.728033	W/Tr
DC	36.798743	W/Tr
SW(on)	3.634458	W/Tr
SW(off)	1.093576	W/Tr
$\Delta T_{J-c}(Ave)$	6.644284	$^{\circ}C$
$T_J(Ave)$	69.102317	$^{\circ}C$

B **Di**

P-Di	12.921325	W/Di
SW	0.419581	W/Di
DC	12.501744	W/Di
$\Delta T_{J-c}(Ave)$	2.713478	$^{\circ}C$
$T_J(Ave)$	56.589876	$^{\circ}C$

C **P_Sum**

P-Sum	326.688607	W
-------	------------	---

D **Save to CSV**

A. Tr (Transistor)

i. P-Tr

- Transistor Total Power Loss per Transistor

ii. SW

- SW(on) + SW(off) of Transistor

iii. DC

- DC Power Loss of the Transistor
- Displays the value of IGBT Power Loss.
- If no computation of IGBT Power Loss it will display a blank result

iv. SW(on)

- Switch On Power Loss
- Displays the value of Switch On Power Loss.
- If no computation of Switch On Power Loss it will display a blank result

- v. SW(off)
 - Switch Off Power Loss
 - Displays the value of Switch Off Power Loss.
 - If no computation of Switch Off Power Loss it will display a blank result

- vi. ΔT_{j-c} (Ave)
 - Difference between Junction Temperature and Case Temperature of Transistor

- vii. T_j (Ave)
 - Junction Temperature of Transistor
 - Displays the value of IGBT Temperature.
 - If no computation of IGBT Temperature it will display a blank result
 - If IGBT Temperature exceeded the maximum Junction temperature of a device/module, a warning message will be prompt

- B. Di (Diode)
 - i. P-Di
 - Diode Total Power Loss per Diode

 - ii. SW
 - Recovery Power Loss
 - Displays the value of Recovery Power Loss.
 - If no computation of Recovery Power Loss it will display a blank result

 - iii. DC
 - DC Power Loss of the Diode
 - Displays the value of FWD Power Loss.
 - If no computation of FWD Power Loss it will display a blank result

 - iv. ΔT_{j-c} (Ave)
 - Difference between Junction Temperature and Case Temperature of Diode

 - v. T_j (Ave)
 - Junction Temperature of Diode
 - Displays the value of FWD Temperature.
 - If no computation of FWD Temperature it will display a blank result
 - If FWD Temperature exceeded the maximum Junction temperature of a device/module, a warning message will be prompt

C. P-Sum

- Total Power Loss
- For Chopper, $P\text{-Sum} = P\text{-Tr} + P\text{-Di}$
- For 3-Phase-Inverter, $P\text{-Sum} = 6 \times (P\text{-Tr} + P\text{-Di})$

D. Save To CSV

- Saves Computation to CSV
- Saves the Display Power Loss Result, Module/Device Constant, User Input Parameters and Computation.
- No CSV data will be generated if error occurs during computation

Release Note

2015 / 04 / 10

v 1.0

First release

Notes

- 1) The information contained herein is subject to change without notice.
- 2) Before you use our Products, please contact our sales representative and verify the latest specifications :
- 3) Although ROHM is continuously working to improve product reliability and quality, semiconductors can break down and malfunction due to various factors.
Therefore, in order to prevent personal injury or fire arising from failure, please take safety measures such as complying with the derating characteristics, implementing redundant and fire prevention designs, and utilizing backups and fail-safe procedures. ROHM shall have no responsibility for any damages arising out of the use of our Products beyond the rating specified by ROHM.
- 4) Examples of application circuits, circuit constants and any other information contained herein are provided only to illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.
- 5) The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM or any other parties. ROHM shall have no responsibility whatsoever for any dispute arising out of the use of such technical information.
- 6) The Products are intended for use in general electronic equipment (i.e. AV/OA devices, communication, consumer systems, gaming/entertainment sets) as well as the applications indicated in this document.
- 7) The Products specified in this document are not designed to be radiation tolerant.
- 8) For use of our Products in applications requiring a high degree of reliability (as exemplified below), please contact and consult with a ROHM representative : transportation equipment (i.e. cars, ships, trains), primary communication equipment, traffic lights, fire/crime prevention, safety equipment, medical systems, servers, solar cells, and power transmission systems.
- 9) Do not use our Products in applications requiring extremely high reliability, such as aerospace equipment, nuclear power control systems, and submarine repeaters.
- 10) ROHM shall have no responsibility for any damages or injury arising from non-compliance with the recommended usage conditions and specifications contained herein.
- 11) ROHM has used reasonable care to ensure the accuracy of the information contained in this document. However, ROHM does not warrant that such information is error-free, and ROHM shall have no responsibility for any damages arising from any inaccuracy or misprint of such information.
- 12) Please use the Products in accordance with any applicable environmental laws and regulations, such as the RoHS Directive. For more details, including RoHS compatibility, please contact a ROHM sales office. ROHM shall have no responsibility for any damages or losses resulting from non-compliance with any applicable laws or regulations.
- 13) When providing our Products and technologies contained in this document to other countries, you must abide by the procedures and provisions stipulated in all applicable export laws and regulations, including without limitation the US Export Administration Regulations and the Foreign Exchange and Foreign Trade Act.
- 14) This document, in part or in whole, may not be reprinted or reproduced without prior consent of ROHM.



Thank you for your accessing to ROHM product informations.
More detail product informations and catalogs are available, please contact us.

ROHM Customer Support System

<http://www.rohm.com/contact/>